

DC 4000

Description

A clear Anti Graffiti film, used for protection from vandalism, can be applied to glass and some smooth surfaces.

Benefits

- Ideal for long-term protection against the scratching of external glass surfaces, facing pedestrian traffic areas, such as: display windows, advertising signage, advertising displays, etc.
- Low-cost alternative to glass replacement due to scratching.
- Genuine, industry-leading three-year external warranty.
- Patented “external” pressure sensitive adhesive.
- Patented “external” scratch resistant coating.
- Almost 3 times as thick as normal film.
- Holds shattered glass together, reducing risk of injury.

Application

Clear Float or Laminated	YES
Tinted Float or Laminated	YES
Toughened	YES
Wire Cast	YES

For thickness and colour, see sample DC2645

Specifications

1. Solar Heat Rejection	22%
2. Glare Rejection	3%
3. Ultra Violet Rejection	99%+
4. Light Transmittance	85%
5. Solar Transmittance	76%
6. Solar Reflectance	8%
7. Solar Absorbance	16%
8. Visible Light Reflectance	9%
9. Shading Co-efficient	0.91
10. U-Value (W/Sq.m.k.)	5.8
11. Emissivity	0.90
12. Colour	Clear
13. Film Construction	Clear Film
14. Visual Characteristics	Non Reflective
15. Laminates	Single
16. Metal Type	No Metal
17. Scratch Resistant	Yes
18. Thickness (Microns)	100
19. Warranty	- 3 years Commercial/ Residential - 12 Months Workmanship
20. EMF Rating	- Low Energy Consumption - up to 15% FIR retention
20F. SHGC	78

Physical Properties

a. Tensile Strength	33,100 Pounds per square inch
b. Break Strength	132 Pound force per inch width
c. Elongation at Break	167%
d. Peel Strength	3200 Grams per inch width
e. Puncture Strength	74 Pounds force

* In certain applications a thermal safety assessment recommendation is required prior to application.

Refer to Film Specifiers Guide for further information.

damage control window films specification sheet

**protect
your home
& your
business.**